



DATAGRAM

Duro-Perm[®] Adhesive

Product Description

Duro-Perm[®] adhesive is a non-flammable, solvent type asphalt adhesive containing no harmful fibres.

Features and Benefits

- ◆ Excellent fire resistive properties.
- ◆ Can be applied mechanically or with brush or roller.
- ◆ Winter or summer viscosities for ease of spreadability.
- ◆ Convenient 18.93 litre pail packaging

Uses

Duro-Perm[®] adhesive is used as a bonding agent to adhere Duro-Perm[®] vapour retarder to the deck and to seal both side and end.

Standards, Listings and Approvals

- ◆ Component for use in the following assemblies:
 - CAN/ULC S126-M86
 - CAN/ULC S107-M87
 - CAN4-S101-M82
- ◆ FM approved as a component for use in class 1 Insulated roof assemblies, 1-60 and 1-90 windstorm rated.



Physical Properties

Physical Properties	Regular Grade Specifications	Winter Grade Specifications
Color	Black	Black
Viscosity @ 25°C (77°F)	2200 / 6000 cps	700 / 1600 cps
Total solids	60% (approx.)	60% (approx.)
Specific gravity	1.16 kg/L (11.6 lbs / gal)	1.18 kg/L (11.8 lbs / gal)
Flammability (Wet)	Non-flammable	Non-flammable
Packaging	18.93 L (4.54 gal) pails	18.93 L (4.54 gal) pails
Application rates		
Vapour Retarder to steel decks	0.16 L/m ² (0.33 gal / 100 sq.ft.)	0.16 L/m ² (0.33 gal / 100 sq.ft.)

Limitations

Solvent in product attacks polystyrene insulation. Avoid use where solvent odours may taint food or other susceptible products. Do not use on steel having a polyvinyl chloride plastic finish.

Typical physical properties or performance characteristics described herein are based upon data derived under controlled conditions. Beacon assumes no liability for design or construction by others, improper storage, handling, or installation on the job site. This data and information may be subject to change; consult Beacon for further information.